




C&I Series Hybrid Inverter

25-50KW Hybrid Inverter

Commercial | Three Phase | HV Battery | 4 MPPTs

SMART ENERGY
SUSTAINABLE SOLUTIONS ”



Talented

- 98.8% max. efficiency
- 135-750V super wide battery voltage range
- Max. 100A charge/discharge current
- Max. 30A PV input current
- Within 20ms UPS-level switching

Reliable

- IP65 protection degree
- Compact and elegant appearance with advanced structure design
- Long-term efficient operation with advanced heat dissipation design
- Outstanding working performance thanks to HANCHU platform

Powerful

- Up to 100% unbalanced load
- Up to 110% AC output overloading
- Max. 120% back-up output overloading @60s
- Parallel operation capacity support system size from KW to MW level

Friendly

- Convenient installation and O&M with horizontal design and quick plug terminals
- Easy data check via both OLED display and App
- Intelligent energy management with HANCHU built-in EMS
- Easy Wifi configuration via App

C&I Series Hybrid Inverter

Type Designation	CESS-HY-25K	CESS-HY-30K	CESS-HY-36K	CESS-HY-40K	CESS-HY-50K
PV Input					
Max. Input Power	37.5kW	40.5kW	54.0kW	60.0kW	75.0kW
Start-up Voltage	135V				
Max. DC Input Voltage *	1000V				
Rated DC Input Voltage	620V				
MPPT Voltage Range *	200-850V*				
No. of MPP Trackers	4				
No. of DC Inputs per MPPT	2				
Max. Input Current	30×4A				
Max. Short-circuit Current	40×4A				
Battery Side					
Battery Type	Lithium Battery (with BMS)				
Battery Voltage Range	135-750V				
Max. Charge/Discharge Current	100/100A				
Grid Side					
Rated Output Power	25.0 kW	30.0 kW	36.0 kW	40.0 kW	50.0 kW
Max. Output Apparent Power	27.0kVA	33.0/30.0 ¹⁾ kVA	39.6kVA	44.0kVA	55.0kVA
Max. Input Apparent Power **	30.0kVA	36.0kVA	43.5kVA	48.0kVA	60.0kVA
Max. Charging Power of Battery	25.0 kW	30.0 kW	36.0 kW	40.0 kW	50.0 kW
Rated AC Voltage	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated AC Frequency	50 Hz / 60 Hz				
Max. Output Current	42.0 A	50.0/43.5 ²⁾ A	60.0 A	66.0 A	83.0 A
Power Factor	0.8 leading ... 0.8 lagging				
Max. Total Harmonic Distortion	<3% @Rated output power				
DCI	<0.5%In				
Back-up Side					
Rated Output Power	25.0kW	30.0kW	36.0kW	40.0kW	50.0kW
Max. Output Apparent Power	27.5 kVA	33.0 kVA	39.6 kVA	44.0 kVA	55.0 kVA
Max. Output Current	42.0A	50.0 A	60.0 A	66.0 A	83.0 A
UPS Switching Time	<20ms				
Rated Output Voltage	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated Output Frequency	50 Hz / 60 Hz				
Peak Output Apparent Power***	30, 60s kVA	36, 60s kVA	43.5, 60s kVA	48, 60s kVA	60, 60s kVA
Voltage Harmonic Distortion	<3% @Linear load				
Efficiency					
Max. Efficiency	98.8 %				
European Efficiency	98.3 %				



Product Info



Official Website

info@hanchuess.com
 0510-88865288
 www.hanchuess.com

No.9 Huicheng Road, Huishan District, 214177 Wuxi, Jiangsu, China

C&I Series Hybrid Inverter

Type Designation	CESS-HY-25K	CESS-HY-30K	CESS-HY-36K	CESS-HY-40K	CESS-HY-50K
Protection					
DC Reverse Polarity Protection				Integrated	
Battery Input Reverse Connection Protection				Integrated	
Insulation Resistance Protection				Integrated	
Surge Protection				Integrated	
Over-temperature Protection				Integrated	
Residual Current Protection				Integrated	
Islanding Protection				Integrated	
AC Over-voltage Protection				Integrated	
Overload Protection				Integrated	
AC Short-circuit Protection				Integrated	
General Data					
Over Voltage Category				PV: II; Main: III	
Dimensions (W×H×D)				800*620*300mm	
Weight				76.0kg	
Protection Degree				IP65	
Standby Self-consumption				<15W	
Topology				Transformerless	
Operating Temperature Range				-30~60°C	
Relative Humidity				0-100%	
Operating Altitude				3000m (>3000mderating)	
Cooling				Smart Fan	
Noise Level				<50dB	
Display				OLED & LED	
Communication				CAN, RS485,WiFi/LAN (Optional)	
Certifications				IEC/EN 62109, IEC/EN 61000, EN50549-1, TOR Generator Type A, VDE-AR-N-4105	
Warranty				12 years	

* Max. operating DC voltage is 950V, max. withstanding DC voltage is 1000V

** Max apparent power from the grid means the maximum power imported from the utility grid used to satisfy the backup loads and charge the battery

*** The output power will exceed the rated value only when the power in the PV array is sufficient, and the duration of the overload is related to the overload power

1) AS 4777.2: 30.0kVA; 2) AS 4777.2: 43.5A



Product Info



Official Website

✉ info@hanchuess.com ☎ 0510-88865288 🌐 www.hanchuess.com

📍 No.9 Huicheng Road,Huishan District,214177 Wuxi, Jiangsu, China